

## Features

- Hot-swap design for easy management
- Zoning support for easy deployment
- Intelligent enclosure management
- 6 external SAS ports for host and expansion
- Redundant power supply
- Tool-less drive trays



## Applications :

Near-line database expansion storage • High performance direct attached storage for HPC or application server • Virtual Tape Library • Multimedia On Demand • Online E-mail Storage • Local storage for video post-productions • Digital content source database storage • Private / Public cloud Expansion

## Specifications

<b>General</b>	JBOD	<b>Hot swap and Redundancy</b>	Disk Drive: Hot swap 60-bay Cooling: 4 x 8038 hot swap fans Power Supply: 549W 1+1 hot swap redundant 80+ Platinum Power Entry: Dual AC Inlet
<b>Platform</b>	4U 60x 3.5 SAS/SATA hard drives	<b>Electrical and Environmental</b>	Universal A/C Input 100~240V AC full range Operating Environment: Temperature : 0°C to 35°C Relative humidity : 20% to 80% Non-operating Environment: Temperature :-20°C to 60°C Relative humidity : 10% to 90%
<b>Number of Expander</b>	Single	<b>Physical Specification</b>	Dimensions: inches : 17.1 x 31.3 x 6.9 Gross Weight (w/ PSU, w/o Rail & Disks) lbs : 71.4 Packaging Dimensions: inches : 24.2 x 43.8 x 16.8
<b>Expander Chip</b>	LSI SAS3x36R	<b>Mounting</b>	Standard 36" slide rail
<b>Host/ Expansion Interface</b>	3 x Mini SAS HD (SFF-8644)		
<b>Drive Interface</b>	12Gb & 6Gb SAS/SATA using single expander		
<b>Admin/ Management</b>	Admin/Firmware Upgrade In-band & Serial port interface IEM port (Optional) LED indicators, Audible Alarm		